

Windshield/ Rear Window Install

INST-3100

PART NUMBERS

3100, 3101, 3102,
3103, 3104, 3124,
3126, 80999, 80106

PAGE 1 OF 1

#@\$!*@#\$\$ INSTRUCTIONS

MID FIFTY F-100 PARTS 1-800-252-1956

Windshield is installed from OUTSIDE truck, rear window is installed from INSIDE. Do NOT use silicone or glue, Always use butyl (3126), correct size rope (3124) a bag of rubber gloves (80099-M or L), razor blades (80106), a bottle of Windex and large roll or paper towels. Butyl does not "dry" use a small bead but expect to run your clean up around the glass about 500 times or a whole roll of paper towels, and, again later when everything settles and gets warm.

Writing this up I realized this is quite a few little things and they add up, so, ever your supplier, I put together a little kit, includes everything but the Windex and Paper towels. After a trip to my nearest Home Depot, I find I can sell it for over \$10.00 cheaper than if you bought them there.

REAR WINDOW, see also illustrations (letters) in our catalog.

- 1..The rubber is the same all around, there are no corners
- 2..The Glass is larger than the opening
- 3..The Rear glass is installed on INSIDE of truck.
- 4..You are pulling rope from OUTSIDE of truck (B)
- 5..The larger part of the rubber (D) goes INSIDE truck
- 6..The smaller part of rubber (C) goes OUTSIDE truck
- 7...**If you install it backwards, then call and tell us there is something wrong with rubber or that glass is too big for hole, etc.
well then...We know that you did not read the directions, AND, you owe us lunch, if you are a professional glass installer, we will be expecting dinner!

WINDSHIELD is installed from OUTSIDE.

WRAP AROUND REAR WINDOW RUBBER installs like WINDSHIELD

Both are installed from OUTSIDE truck.

Install in this order; Rubber on Glass, Trim in Rubber, Entire assembly into truck.